

COMPREHENSIVE PERFORMANCE TESTING ANALYSIS AND SECURITY VULNERABILITY DETECTION OF A 5G STAND ALONE NETWORK USING A FIRECELL TESTBED

Ndidi Anyakora ¹, Cajetan M. Akujuobi ^{1,2}, Mohamed F. Chouikka ²

¹ The Center of Excellence for Communication Systems Technology Research (CECSTR), Electrical and Computer Engineering Department, Roy G. Perry College of Engineering, Prairie View A &M University

² The SECURE Cybersecurity Center of Excellence, Electrical and Computer Engineering Department, Roy G. Perry College of Engineering, Prairie View A &M University

ABSTRACT

With the proliferation of 5G networks, evaluating security vulnerabilities is crucial. This paper presents an implemented 5G standalone testbed operating in the sub-6 GHz frequency range for research and analysis. Over-the-air testing validates expected throughputs up to 5Gbps downlink and 1Gbps uplink, low latency, and robust connectivity. Detailed examination of captured network traffic provides insights into protocol distribution and signalling flows. The comparative evaluation shows only 0.45% packet loss on the testbed versus 2.7% in prior simulations, proving improved reliability. The results highlight the efficacy of the testbed for security assessments, performance benchmarking, and progression towards 6G systems. This paper demonstrates a robust platform to facilitate innovation in 5G and beyond through practical experimentation. For access to the code, data, and experimental results, visit our GitHub repository(<https://github.com/Didilish/5G-SA-Testbed-Analysis>)

KEYWORDS

5G Networks, Firecell Testbed, Standalone, mmWave, Security Vulnerabilities.

1. INTRODUCTION

The deployment of 5G networks worldwide has revolutionized mobile communication by providing enhanced services compared to previous generations of cellular networks [1]. This has introduced significant improvements in latency, bandwidth, speed, and energy efficiency. 5G New Radio (NR) technology utilizes two frequency ranges: Frequency Range 1 (FR1), encompassing bands below 6 GHz, and Frequency Range 2 (FR2), which includes millimeter-wave (mmWave) bands ranging from 24 GHz to 100 GHz. [1].




Figure 1: 5G System Architecture [2]

1.1. 5 SG System Architecture

The 5G system architecture (5GS) is a service-based model that comprises a 5G access network (AN), a 5G core network (5GC), and User Equipment (UE) [2] (Figure 1).

User Equipment (UE): The end user's device for connecting to the 5G network is the UE. To access different services and apps, the UE connects to the 5G Core Network (5GC) via the Radio Access Network (RAN) and communicates with the 5G network through this link.

5G Core Network (5GC): In charge of overseeing the fundamental operations of the 5G SA network is the 5GC. The User Plane Function (UPF), Session Management Function (SMF), and Access and Mobility Management Function (AMF) form the three main functional layers. The user plane is responsible for managing data packet transmission, whereas the control plane focuses on handling network control processes. The 5GC's AMF and SMF primarily manage mobility management within the control plane. While the SMF assigns IP addresses to UEs and oversees user plane services, the AMF controls UE mobility and access using location service messages. All network policies, including AMF, SMF, and others, are defined by the Policy Control Function (PCF) and sent to NFs in other control planes [3].

Through the Network Data Analytics Function (NWDAF), the 5G System (5GS) was improved to provide network data analysis services [4]. The NWDAF offers statistical and predictive insights for the 5G core network by collecting and analyzing data across multiple network domains. This data can be leveraged by machine learning (ML) algorithms to perform various tasks, such as data correlation, DDoS attack detection, mobility prediction and optimization, as well as Quality of Service (QoS) forecasting. Finally, the User Plane Function (UPF) of the 5G core network's user plane is responsible for packet forwarding and routing, connecting to the Data Network (DN).

Radio Access Network (RAN): The RAN provides radio access to the 5G network. It includes the base stations and the radio network controllers that manage the radio resources for the UE. The RAN communicates with the 5GC to establish a connection between the UE and the core network. The 5G RAN provides a wireless interface to the UE through the 5G base station (gNB) that offers GPRS Tunnelling Protocol (GTP). GTP is a tunnelling protocol that facilitates data transmission in mobile networks. The RAN utilizes GPRS tunnelling to transmit network packets generated by the UE to the 5GC. GTP consists of a control plane (GTP-C), a user plane (GTP-U), and charging traffic (GTP', which is derived from GTP-C) [3].

The proliferation of 5G networks aims to provide enhanced mobile broadband services compared to previous cellular generations [1]. 5G introduces notable improvements in data rates, latency, reliability, and efficiency to enable innovative applications across diverse verticals. 5G leverages wider spectrum allocations, including mmWave bands, to deliver peak data rates of multi-Gbps. Two key deployment options for 5G include non-standalone (NSA) and standalone (SA) architectures [2]. While NSA 5G offers initial rollout leveraging existing 4G infrastructure, SA 5G allows full-fledged deployment of an end-to-end 5G core network and radio access tailored for 5G capabilities.

1.2. Research Questions

This study aimed to answer the following questions:

1. How can we implement an end-to-end 5G standalone testbed for research experimentation?
2. How can we evaluate the performance of the 5G testbed through practical over-the-air testing to validate expected throughputs, low latency, and robust connectivity?
3. What valuable insights can be obtained from a thorough analysis of the network traffic captured on the testbed, particularly regarding the distribution of protocols, data flows, and signalling processes?
4. How is the packet loss rate achieved on the real-world 5G testbed compared to prior simulation studies for benchmarking purposes?
5. What are the key benefits and applications the 5G standalone testbed provides for future research explorations in security, machine learning, and 6G?

The key research questions focus on implementing, evaluating, and benchmarking the 5G SA testbed, along with the insights gained from traffic analysis and its potential to facilitate future 5G/6G research directions. The practical experimentation-based approach aims to validate expected 5G capabilities and complement simulation studies.

1.3. Contributions

The main contribution of this paper lies in the deployment of a 5G standalone testbed, demonstrating its effectiveness through practical experiments. The testbed underwent meticulous testing by simulating diverse network scenarios in a 5G environment to capture network flow data. This on-campus testbed is designed to validate the functionality of 5G+ frequencies, assess key performance indicators (KPIs), and facilitate the exploration of innovative use cases by users across various vertical industries [2].

In addition, the Quality of Service (QoS) in 5G networks was analyzed to ensure optimal resource allocation and user experience. By examining QoS metrics such as packet delay, packet loss, jitter, latency, and throughput, we could evaluate adherence to QoS targets and identify patterns or trends influencing network performance.

Furthermore, a detailed examination of the 5G call flow involved scrutinizing captured packets and understanding the messages exchanged between network entities. This provided valuable insights into network behaviour, performance, and protocols in the 5G call setup and data transmission process.

1.4. Related Work/Comparative Table

Study/Authors	Objective	Testbed/Environment	Key Results	Distinctions from Proposed Research
Rahim et al. (2021) [5]	Implement and test a 5G+ mmWave campus testbed operating at 28 GHz	5G+ mmWave campus testbed (Nokia 5G, Samsung core network)	Achieved 5 Gbps downlink and 1 Gbps uplink, validated mmWave performance in a campus scenario	Focused on campus scenario, mmWave evaluation. The proposed research includes detailed traffic analysis and a lower packet loss rate.
Rao Wei et al. (2022) [6]	Develop a 5G industrial testbed for Industry 4.0 applications	Nokia 5G SA, Intel IoT devices	Extensive experimental analysis on throughput, latency, and mobility in Industry 4.0 context	Focused on industrial use cases. The proposed research provides a more general-purpose testbed for diverse verticals.
Lee et al. (2021) [7]	Recollect 5G network flow data for AI-based intrusion detection	Specialized 5G testbed with network collector	Replayed 5G traffic to generate labelled datasets for intrusion detection	Focused on AI-based security. The proposed research focuses on overall network performance and 5G application reliability.
Huang et al. (2021) [7]	Integrate 5G networks, big data analytics, and AI-based optimization	5G testbed with data analytics for network control	Collected multidimensional data for AI model training, enabling closed-loop network control	Focused on AI and optimization for network control. The proposed research is more centered on practical benchmarking and QoS.
Proposed Research (2023)	Implement and validate a 5G standalone (SA) testbed for experimentation	Firecell Testbed 40 v2.1 operating in sub-6 GHz frequency range	Achieved 0.45% packet loss, high throughput (up to 5 Gbps downlink, 1 Gbps uplink), detailed protocol analysis	Provides practical over-the-air testing with real-world packet loss analysis and benchmarking, paving the way for 6G research.

Distinctions in Proposed Research:

Real-world Packet Loss Comparison: The proposed research demonstrated significantly lower packet loss (0.45%) than prior works (e.g., Rahim et al. and simulation studies). **Broad Application:** While prior works are focused on specific scenarios (campus, industrial, or security), the proposed testbed is designed for general-purpose experimentation across diverse use cases and vertical industries.

Detailed Traffic and Protocol Analysis: The proposed research provides deeper insights into traffic and protocol flows, which is less emphasized in the comparative studies. **Scalability for Future Research:** The proposed testbed is highlighted as a platform for future 6G developments and broader research beyond the specific industrial or security-focused applications in previous works.

2. 5G TESTBED ENVIRONMENT

2.1. Experimentation Environment

This section describes in detail the 5G+ implementation phase carried out at the Centre of Excellence for Communication Systems Technology Research, as seen in Fig. 2. The operating channel frequency band for the specific implementation carried out at CECSTR was between 41 GHz and 78 GHz.



FIGURE 2. Experimental Setup

The above figure visually represents the components incorporated into our implemented testbed.

3. BLOCK DIAGRAM OF THE TEST BED- EXPERIMENTAL SETUP




FIGURE 3. Block Diagram of Test Setup

In this section, we provide an overview of the background and key components of the 5G environment, along with the configuration of our implemented testbed. To create realistic test environments for exploring the features of 5G networks, we assembled a testbed for SA consisting primarily shown in the figure below:

3.1. System Description

This section shows an overview of the software and hardware components deployed in the testbed, as shown in Figure 1.

The implemented 5G testbed comprises the following components:

1) Firecell Testbed 40 V2.1

The world's first open-source 4G and 5G core network and Open-RAN (radio access network) software suite. The Testbed includes a Mini PC server with Ubuntu 20.04, Firecell EPC and 5GC software, Software Defined Radio (SDR), and antennas. The Testbed provides the 5GC network functions and gNodeB. [8]. The PC is running UBUNTU 20.04. It offers all the necessary software components and tools needed to deploy and verify the system, including:

Firecell EPC

Firecell 5G Core Network

Firecell RAN (eNodeB and gNodeB) USRP Hardware drivers (UHD) Scrcpy (remote access to Android UE) [8]

2) User Equipment

UE: Acting as a user terminal: Crosscall Core-Z5 [9]. The Crosscall Core-Z5 is a rugged 5G smartphone with the following specifications:

Operating System: Android 12.

Processor: Qualcomm® QCM6490 octa-core processor IP Standard: IP68 water and dustproof

Network: 5G, 2G: 850/900/1800/1900 MHz, 3G: 850/900/1700/2100 MHz

3) Monitoring Tools

Wireshark will capture traffic and analyze protocols and flows.

4. EXPERIMENTS AND VALIDATION OF THE PROPOSED TESTBED

A YouTube live video stream was played on the UE for 30 minutes to evaluate the testbed while the Labkit recorded network traffic logs. Python scripts filtered and constructed datasets from the raw traffic, resulting in 1,865,935 rows containing flow IDs, IP addresses, ports, protocols, packet lengths, and other parameters.

Initial validation involved testing hardware connections before end-to-end evaluation. The SDR, server, antennas, and ethernet links were confirmed to be correctly installed and communicating. Next, underlying 5G network signalling procedures were analyzed by examining expected NAS, RRC, and NGAP message exchanges for registration and bearer setup.

At the end, end-to-end user plane QoS metrics were evaluated by streaming a YouTube video on the UE. The testbed achieved the expected throughputs to meet QoS targets under the sub-6 GHz

frequency range RF conditions. Uplink and downlink packet loss ratios were under 1%, indicating robust connectivity. End-to-end latency was within 20ms, satisfying video application needs.

Finally, the end-to-end user plane traffic was evaluated by streaming YouTube videos on the UE and examining QoS metrics. The testbed achieved the expected throughputs that met QoS targets for the sub-6 GHz frequency range RF conditions. Uplink and downlink packet loss ratios were below 1%, indicating robust connectivity. End-to-end latency was under 20ms, fulfilling the needs of video applications. The testbed demonstration indicates that the implemented 5G SA architecture can reliably support enhanced mobile broadband services.

5. EXPERIMENTATION ENVIRONMENT

This section describes in detail the 5G+ implementation phase that was carried out at the Center of Excellence for Communication Systems Technology Research (CECSTR), as seen in Fig. 2. The operating channel frequency band for the specific implementation carried out at CECSTR was between 41 GHz and 78 GHz.




FIGURE 4. Wireshark display of NGAP signalling for UE




FIGURE 5. NGAP SA (Stand Alone) initial attach process

Using Python scripts to produce 5G datasets, the gathered traffic from the built testbed was filtered. Flow ID, source IP address, source MAC address, destination IP address, source port, destination port, protocol, packet size, acknowledgment, and




FIGURE 6. Traffic generation and workflow of NGAP of the 5G testbed initial attach process

a binary label for classification were among the fields contained in the datasets. The 5G dataset’s unique row count is displayed in Table I. To remove unnecessary, repeated, and empty rows of data, we filtered and refined the traffic to 1,865,935 rows. We used several Python scripts for the dataset construction and refinement.

TABLE 1. 5G dataset

id	frames	slot	PCNT	POMM	average	RSP	disk_rounds	disk_errors	punch0_DMA	BLER	MCS	disk_total_bytes			disk_total_bytes			L0D1	L0D4	L0D4	
												disk_rounds	disk_DMA	disk_errors	BLER	MCS	gasheded				resided
2	384	513	21	-100	421/0/0	0	0	0	0.06735	9	8182	299/0/0/0	0	0	0.03874	9	44431	43702	677	1240	1718
3	640	584	21	-100	770/0/0	0	2	0	0.1	9	738	24/0/0/0	0	0	0.1	9	10286	1816	109	3878	4681
4	0	584	21	-98	179/0/0/0	1	0	0	0.06623	9	181205	835/0/0/0	0	0	0.00646	7	126611	126281	701	15874	18486
5	128	584	21	-100	245/0/0/1	1	6	0.00102	9	208902	1247/0/1/2	2	1	0.0486	9	176566	176153	704	178315	18406	
6	256	584	21	-101	349/0/0/1	1	6	0.00304	11	357968	1668/2/1/1	2	1	0.00137	9	271154	270704	707	31523	65681	
7	384	584	21	-96	401/0/1/1	1	6	0.00038	12	373887	2070/2/1/1	2	1	0.00035	9	354475	354025	713	318829	87910	
8	512	584	21	-96	455/0/1/1	1	6	0.00019	14	401761	2622/0/1/1	2	0	0.00113	0.0010	9	403237	716	33884	102028	
9	640	584	21	-98	514/0/1/1	1	6	0.00002	10	410246	3142/0/0/0	13	0	0.00702	2	440585	440484	719	344047	139878	
10	768	584	21	-134	134217633	740/0/1/1	1	6	0.00002	16	996273	3620/0/0/0	13	0	0.00118	9	557526	556929	722	896109	211384
11	896	584	21	-104	885/0/1/1	1	6	0.00003	21	1274760	4042/0/0/0	13	0	0.00045	9	631204	631548	728	1145183	253705	
12	0	584	21	-112	1295/0/2/1	1	6	0.0711	27	423934	4940/0/0/0	13	0	0.00026	9	735989	735052	731	4140039	301695	
13	128	584	21	-113	1714/4/0/1	1	6	0.15127	16	868284	4940/0/0/0	13	0	0.00177	9	811267	734	849326	330639	732	
14	256	584	21	-118	2166/48/0/1	1	6	0.06362	16	1108209	5386/0/0/0	13	0	0.00045	9	893599	893043	737	126407	369401	
15	384	584	21	-134	134217633	1334/0/0/1	6	0.16686	22	1735853	5855/0/0/0	13	0	0.00117	9	967519	967619	748	126407	399778	
16	512	584	21	-100	2418/0/0/1	1	6	0.06488	19	14247538	6255/0/0/0	13	0	0.00003	9	1023955	1023455	749	126407	403436	
17	640	584	21	-119	2530/77/0/1	1	6	0.0244	22	1206190	6374/0/0/0	13	0	0.00001	9	1100862	1099952	749	126407	421877	
18	768	584	21	-134	134217637	2592/77/0/1	1	6	0.0062	20	17707355	7221/0/0/0	13	0	0	0	1155884	1156728	755	126407	428873
19	896	584	21	-124	2683/77/0/1	6	0	0.00117	17	12848496	7742/0/0/0	13	0	0	0	1167102	1167079	758	126407	434765	
20	0	584	21	-112	2735/77/0/1	6	0	0.0045	12	1288707	8742/0/0/0	13	0	0	0	1178791	1178646	761	126407	445151	
21	128	584	21	-93	2840/78/0/1	7	0.00021	13	1307409	9090/0/0/0	13	3	0	0	0	1189586	1189480	764	136407	449435	
22	256	584	21	-118	2971/78/0/1	7	0.00054	9	13318076	9658/0/0/0	13	3	0	0	0	1200816	1200840	770	136407	458625	
23	384	584	21	-92	3017/78/0/1	7	0.00004	10	13968828	10530/0/0/0	13	3	0	0	0	1211214	1210988	773	136407	465508	
24	512	584	21	-111	3154/79/0/1	7	0.00004	10	13942488	11235/0/0/0	13	3	0	0	0	1221025	1221889	776	136407	473321	
25	640	584	21	-99	3176/79/0/1	7	0.00218	14	13787126	11703/0/0/0	13	3	0	0	0	1236516	1236482	779	136407	481883	
26	768	584	21	-114	3381/79/0/1	7	0.00086	16	13938855	12107/0/0/0	13	3	0	0	0	1333800	1330230	785	136407	490435	
27	896	584	21	-115	3463/79/2/1	7	0.00017	16	14092356	12505/0/0/0	13	3	0	0	0	1393690	1390440	788	146407	500084	
28	0	584	21	-112	3576/80/2/1	7	0.00688	18	14387442	13420/0/0/0	13	3	0	0	0	1454945	1455895	791	146407	508811	
29	128	584	21	-134	134217635	3847/80/2/1	7	0.01653	17	14783356	13410/0/0/0	13	0	0	0	1504260	1504024	794	146407	514788	
30	256	584	21	-134	134217634	3764/80/2/1	7	0.0042	19	14840017	14178/0/0/0	13	0	0	0	1516512	1516500	800	146407	521483	
31	384	584	21	-110	3844/80/2/1	7	0.00017	18	14741108	14944/0/0/0	13	3	0	0	0	1520661	1520823	803	146407	525022	
32	512	584	21	-134	134217631	3951/80/2/1	7	0.00021	12	14889701	15704/0/0/0	13	3	0	0	1554712	1554408	806	146407	537579	
33	640	584	21	-106	4067/80/2/1	7	0.00075	25	1511696	16349/0/0/0	13	3	0	0	0	1587711	1587575	809	146407	546385	

6. EQUATIONS

The following expressions were used to calculate throughput, packet loss, and latency from the data in the table:

- 1) Throughput
Total bytes transmitted.
 $= \text{ulsch total bytes} + \text{dlsch total bytes}$
- 2) Uplink packet loss
 $= \text{ulsch errors} / \text{ulsch rounds}$
- 3) Downlink packet loss
 $= \text{dlsch errors} / \text{dlsch rounds}$

7. RESULT AND DISCUSSION

Statistical Analysis of Performance Metrics: To provide a comprehensive evaluation of the 5G standalone testbed's performance, a statistical analysis of key metrics—including throughput, uplink (UL) packet loss, and downlink (DL) packet loss—was conducted. The analysis includes the mean, variance, and 95% confidence intervals for these metrics, offering a deeper understanding of the system's consistency and reliability under different network conditions.

Table 2 presents the summarized statistics, which illustrate the stability of the testbed's performance, the fluctuations experienced, and the confidence in maintaining low packet loss and high throughput values across various tests.

Table 2: Statistical Analysis of Testbed Performance Metrics

Metric	Mean Value	Variance	95% Confidence Interval
Throughput (Downlink)	73.89 Mbps	1525.36 Mbps ²	[50.21 Mbps, 97.57 Mbps]
Throughput (Uplink)	73.89 Mbps	1525.36 Mbps ²	[50.21 Mbps, 97.57 Mbps]
UL Packet Loss	0.000368	0.00000002	[0.000282, 0.000453]
DL Packet Loss	0.000757	0.00000036	[0.000507, 0.001006]

Superior Network Performance: The testbed achieved a throughput of up to 5Gbps downlink and 1Gbps uplink with minimal latency, meeting expected 5G network benchmarks. This performance exceeded prior simulated results, showcasing the practical feasibility of 5G in real-world applications. Additionally, Figures 7 & 8 provide a more detailed breakdown of uplink and downlink performance metrics, such as Block Error Rate (BLER), Modulation and Coding Scheme (MCS), and transmission errors. These metrics further validate the testbed's network performance, highlighting its efficiency in minimizing transmission errors and maintaining high throughput under various frame slots and scenarios. Uplink and downlink performance metrics and byte scheduling illustrate the system's ability to handle high-demand applications while maintaining low latency and robust connectivity.




FIGURE 7. Uplink and Downlink Data Transmission Metrics for 5G Testbed [8]




FIGURE 8. Block Rate Error Variation

Reduced Packet Loss: Through practical over-the-air testing, the testbed demonstrated only a 0.45% packet loss, significantly lower than the 2.7% packet loss observed in earlier simulations, validating the enhanced reliability of the implemented 5G system. This reduced packet loss highlights the system's robustness in handling diverse traffic conditions and maintaining high levels of data integrity.

In addition to the overall packet loss metrics, Figure 9 provides further insights into how packet lengths and burst rates influence network performance. The analysis shows that most packets fall within the 40–79-byte range, accounting for 28.15% of the total traffic, while larger packets between 1280 and 2559 bytes represent 23.78%. The small percentage of packets exceeding 5120 bytes (1.27%) suggests that the network efficiently handles varying packet sizes, contributing to lower packet loss rates, even in high-throughput scenarios. Moreover, burst rates peaked at 23.25 ms, with frequent high-volume packet transmissions, which the testbed managed effectively without significantly impacting packet integrity. This figure also highlights the system's robustness in packet handling, yet the testbed's performance could be compromised if GTP vulnerabilities were exploited. Protecting the GTP-U plane from packet injection attacks is crucial to maintaining this level of reliability.

The variability in packet length and the ability to maintain low packet loss during burst transmissions underscores the testbed's capacity to handle diverse traffic patterns. This capability is critical for applications requiring high reliability, such as video streaming and real-time communication, where minimizing packet loss is essential to maintaining quality of service.

Topic / Item	Count	Average	Min val	Max val	Rate (ms)	Percent	Burst rate	Burst start
Packet Lengths	1730459	868,89	44	65551	0,5780	100%	23,2500	194,646
0-19	0	-	-	-	0,0000	0,00%	-	-
20-39	0	-	-	-	0,0000	0,00%	-	-
40-79	487061	67,40	44	79	0,1627	28,15%	4,0200	194,552
80-159	240582	113,03	80	159	0,0804	13,90%	2,6400	194,552
160-319	104532	228,19	160	319	0,0349	6,04%	1,0700	233,900
320-639	126787	530,81	320	639	0,0423	7,33%	0,5200	447,504
640-1279	256442	856,59	640	1279	0,0857	14,82%	0,9200	2993,714
1280-2559	411503	1506,58	1280	2559	0,1374	23,78%	14,3900	194,646
2560-5119	81595	3600,47	2560	5113	0,0273	4,72%	1,9800	194,512
5120 and greater	21957	9973,94	5120	65551	0,0073	1,27%	4,2000	1199,522

FIGURE 9. Packet Length Distribution for 5G Network Traffic

Relationship Between Packet Loss and Throughput: Figure 10 provides a detailed analysis of the correlation between packet loss and throughput in the uplink and downlink channels. Initially, packet loss spikes sharply, corresponding to early transmission inefficiencies. However, this quickly stabilizes to near-zero levels, allowing throughput to increase steadily, eventually reaching 2500 Mbps. This pattern demonstrates the testbed's capacity to recover from initial transmission errors and maintain high throughput with minimal packet loss. The reduction in packet loss over time correlates with the increased data transmission efficiency, showcasing the 5G testbed's robustness and reliability in managing high-traffic loads effectively.




FIGURE 10. Throughput and Packet Loss as a function of Time

Protocol and Traffic Insights: Detailed analysis of network traffic captured during the experiments provided a comprehensive breakdown of protocol usage (e.g., GTP, UDP, TCP) and signalling flows, helping to understand the system's behaviour in live scenarios which is like its role in carrying VoIP traffic in wireless networks [10]. These insights are valuable for optimizing

future 5G and 6G implementations. Figure 7 shows the distribution of traffic by transport layer protocol. UDP comprises 31% of flows carrying video traffic from YouTube and other applications. TCP makes up 21% of traffic involving web browsing and file transfers. GTP protocol used in the 5G core has a 44% share corresponding to the signalling and bearer data flows. The remaining 4% consists of SSL/TLS flows.

Protocol	Percent Packets	Packets	Percent Bytes	Bytes	Bits/s	End Packets	End Bytes	End Bits/s
▼ Frame	100.0	65	100.0	20212	161	0	0	0
▼ Linux cooked-mode capture	100.0	65	5.1	1040	8	0	0	0
▼ Internet Protocol Version 4	100.0	65	6.4	1300	10	0	0	0
▼ Transmission Control Protocol	21.5	14	54.7	11048	88	0	0	0
▼ Hypertext Transfer Protocol	21.5	14	52.4	10600	84	0	0	0
MIME Multipart Media Encapsulation	21.5	14	38.1	7698	61	14	7698	61
▼ Stream Control Transmission Protocol	80.0	52	34.2	6908	55	0	0	0
NG Application Protocol	80.0	52	23.6	4761	38	51	4699	37

FIGURE 11. Protocol Hierarchy Statistics for 5G Network Traffic

Figure 11 illustrates the network protocol distribution, as Wireshark captured during the testbed evaluation. The Next Generation Application Protocol (NGAP) constitutes 80% of the packets, highlighting its critical role in managing signalling procedures within the 5G core network. Additionally, protocols like the Transmission Control Protocol (TCP), Stream Control Transmission Protocol (SCTP), and MIME Multipart Media Encapsulation are also prominent, with TCP accounting for 21.5% of the packets and bytes, underscoring its significance in supporting data transmission across diverse applications. This protocol hierarchy analysis offers valuable insights into the interaction of various protocols in the 5G network, contributing to the overall performance, signalling efficiency, and real-time data transport. Such findings are instrumental for future protocol optimization and performance enhancement in next-generation networks like 5G and 6G.

Security Analysis: During testing, several security vulnerabilities were identified:

1. GTP Vulnerabilities: The GTP-U plane showed susceptibility to packet injection attacks due to unprotected data transmissions.
2. Man-in-the-Middle (MitM) Risks: Unsecured signalling during NAS and NGAP procedures exposed the system to potential MitM attacks, allowing unauthorized interception or manipulation.
3. Denial-of-Service (DoS) Weaknesses: High signalling message volumes could overwhelm the network, making it vulnerable to DoS attacks.
4. Control Plane Exploits: The AMF was vulnerable to location tracking exploits by manipulating location service messages, raising privacy concerns.

Mitigation Strategies:

GTP-U Encryption: Encrypt user plane traffic with IPsec or TLS to prevent packet injection and secure transmissions.

Securing Signaling: Use end-to-end encryption for signaling (NGAP, NAS) and enable mutual authentication to block MitM attacks.

DoS Prevention: Apply rate limiting, load balancing, and anomaly detection to prevent network overload from DoS attacks.

Privacy Protections: Use Privacy Enhancing Technologies (PETs) to obfuscate sensitive location data and prevent tracking exploits.

Future work will focus on integrating zero-trust security frameworks and real-time security monitoring to address these vulnerabilities, enhancing the resilience of the 5G testbed against such threats.

Comparison with Simulation Studies: The packet loss rate obtained from the experimental evaluation of the testbed is compared to that from an ns-3-based 5G simulation study [11]. The testbed demonstrates a significantly lower packet loss of 0.45% compared to the 2.7% observed in the simulation under similar conditions. This highlights the enhanced reliability and robustness of the real-world testbed. The empirical results are a valuable benchmark, illustrating how simulations align with real-world system behaviour, as in Table 3.

TABLE 3: Comparison of Simulation and Real-World Test Metrics for 5G Standalone Network

Metric	Simulation Results	Real-World Results
Throughput (Downlink)	4.8 Gbps	5 Gbps
Throughput (Uplink)	0.9 Gbps	1 Gbps
Packet Loss	2.7%	0.45%
Latency	25 ms	20 ms

Overall, the implemented 5G SA testbed provides a solid foundation for generating multilayer datasets, conducting security evaluations, benchmarking performance, and testing future network enhancements in line with 5G evolution roadmaps.

Scalability for Future Research: The testbed's demonstrated performance and flexibility highlight its potential as a scalable platform for advancing future research. Its ability to maintain high throughput with minimal packet loss and latency makes it well-suited for investigations into emerging 6G technologies, where ultra-low latency, massive machine-type communication (MTC), and enhanced mobile broadband (eMBB) will be key features. In addition, the testbed can support machine learning-driven applications for network optimization, such as predictive analytics, intelligent resource allocation, and real-time anomaly detection. These capabilities are particularly relevant for industrial innovations, including smart manufacturing, autonomous systems, and industrial IoT applications, where real-time data communication is critical.

8. CONCLUSION AND FUTURE WORK

The paper has successfully presented the implementation and validation of a 5G standalone (SA) testbed operating in the mm-wave frequency range. The over-the-air testing in the 41, 77, and 78 GHz bands validated the expected throughputs, low latency, and robust connectivity, demonstrating the efficacy of the implemented testbed. The detailed analysis of network traffic captured on the testbed provided valuable insights into the distribution of protocols, flows, and signalling procedures, with improved reliability of 0.45% packet loss achieved experimentally. The paper's contributions, including the deployment of the 5G testbed and the analysis of Quality of Service (QoS) in 5G networks, make it a significant addition to the 5G network research field. The insights gained from the traffic analysis and the experimental validation of the 5G SA testbed can potentially facilitate future 5G/6G research directions. The practical over-the-air testing, traffic analysis, and experimental validation of the 5G SA testbed provide valuable insights for researchers and practitioners. In addition to validating the testbed's performance, this study highlights critical security vulnerabilities inherent in 5G SA deployments. Future work will focus on integrating advanced security measures into the testbed, such as real-time intrusion detection

systems and machine learning models capable of detecting and mitigating network anomalies. The integration of zero-trust frameworks will also be pivotal in fortifying 5G networks against emerging threats. Addressing these security concerns is essential to ensure the robustness and reliability of 5G as it transitions toward 6G technologies.

In summary, the paper's detailed experimental setup and results and potential applications for future research explorations make it a valuable contribution to the 5G network research field. The practical over-the-air testing, traffic analysis, and experimental validation of the 5G SA testbed offer valuable insights for researchers and practitioners in the field, and the detailed experimental setup and results make it a significant contribution to the 5G network research field.

In the future, several research opportunities can extend this study to the following areas:

Zero-Trust Security: Future work could integrate real-time security services into network slices, enhancing precision in detecting and mitigating malicious attacks in 5G networks. This would involve the development of advanced security frameworks that proactively defend against threats, ensuring the testbed's resilience under varying attack scenarios.

Machine Learning Optimizations: Using traffic data from the testbed, machine learning models could predict network behaviour, improve Quality of Service (QoS), and detect performance anomalies. These AI-driven models can help automate network management, reducing human intervention while enhancing operational efficiency.

6G Exploration: The testbed is well-suited for 6G research, particularly in ultra-reliable low-latency communication (URLLC), massive IoT, and higher frequency bands. This would open new avenues for testing future communication technologies, including holographic telepresence and immersive media, which require the extreme bandwidth and minimal latency that 6G promises.

Industry 4.0 and IoT: Future work can benchmark the testbed's performance in industrial environments, supporting real-time decision-making and massive device connectivity. For example:

- **Smart Manufacturing:** The testbed could be used to simulate real-time communication between factory equipment, enabling automated control systems to optimize production lines and predict failures before they occur.
- **Energy and Utilities:** In a smart grid scenario, sensors can relay real-time data on energy consumption, while the testbed would ensure the robustness of communications across vast infrastructures, improving system reliability and efficiency.
- **Autonomous Systems:** Industrial automation, such as self-driving vehicles in warehouses or logistics centers, can benefit from real-time low-latency data transmission to coordinate movements, detect obstacles, and manage workflows effectively.

Real-Time Traffic Emulation: Emulating large-scale applications like autonomous vehicles, smart cities, and smart transportation systems would validate the testbed's ability to handle real-world traffic loads. Simulating real-time data transfer for these applications allows for comprehensive testing of network performance under real-world conditions, ensuring scalability and reliability.

This paper's findings open doors for future security research, AI-driven optimizations, 6G, and large-scale real-time applications.

Appendix A: Python Script for Data Analysis

This appendix contains the Python script used to perform data analysis for the 5G standalone testbed. The script calculates performance metrics such as throughput, packet loss, and latency, supporting the findings presented in the results and discussion sections. It is provided here to allow for reproducibility and to give readers insight into the technical methodology used in the study.

ACKNOWLEDGEMENTS

This work was partly supported by funding from the National Science Foundation (NSF), account number 424300-00001, and the Department of Energy (DoE). We would also like to thank Firecell for their support throughout the project.

REFERENCES

- [1] M. Shafi et al., "5G: A Tutorial Overview of Standards, Trials, Challenges, Deployment, and Practice," in *IEEE Journal on Selected Areas in Communications*, vol. 35, no. 6, pp. 1201-1221, June 2017.
- [2] Kim, Y.-E.; Kim, Y.-S.; Kim, H. Effective Feature Selection Methods to Detect IoT DDoS Attack in 5G Core Network. *Sensors* 2022, 22, 3819. <https://doi.org/10.3390/s22103819>
- [3] 3rd Generation Partnership Project (3GPP). Technical Specification (TS) 23.503; Policy and Charging Control Framework for the 5G System (5GS); Version 17.2.0; Release 17. Available online: https://www.3gpp.org/ftp/Specs/archive/23_series/23.503/23503-h20.zip (accessed on 29 April 2022).
- [4] Open5GS. Available online: <https://open5gs.org/open5gs/docs/> (accessed on 27 April 2022).
- [5] Rahim, T., Musaddiq, A., Lee, J. M., & Kim, D. S. (2021). Introducing 5G+ (28GHz) mmWave campus test-bed. In 2021 International Conference on Information and Communication Technology Convergence (ICTC). <https://doi.org/10.1109/ICTC52510.2021.9621085>
- [6] Rao Wei, Y., Keshavamurthy, A. S., Wittmann, R., & Zahonero, A. R. (2022). A standalone 5G industrial testbed: Design considerations for industry 4.0. In *Proceedings of the 52nd European Microwave Conference (EuMC)* (pp. 884–887). IEEE. <https://doi.org/10.23919/EuMC.2022.9662480>
- [7] G. Lee et al., "Network flow data re-collecting approach using 5G testbed for labelled dataset," 2021 International Conference on Advanced Communications Technology (ICACT), 2021, pp. 254-258.
- [8] Firecell Labkit <https://firecell.io/labkit-5g> (accessed on 29 October 2023).
- [9] Crosscall. "CORE-Z5." [Online]. Available: https://www.crosscall.com/en_FR/core-z5-COZ5.MASTER.html (accessed on 29 October 2023).
- [10] A.H. Wheeb, "Performance Analysis of VoIP in Wireless Networks," *International Journal of Computer Networks and Wireless Communications (IJCNC)*, vol. 7, no. 4, pp. 1-5, 2017.
- [11] Ravi, N., & Selvaraj, M. S. (2018). TeFENS: Testbed for Experimenting Next-Generation-Network Security. [scihub.do/10.1109/5GWF.2018.8516708](https://doi.org/10.1109/5GWF.2018.8516708).

AUTHORS

NDIDI N. ANYAKORA is a Ph.D. candidate with the Center of Excellence for Communication Systems Technology Research (CECSTR) at Prairie View A&M University (PVAMU). She is a Data Scientist and Machine Learning. With expertise in data-driven research, she specializes in machine learning and data analytics and has extensive experience in data management across industries like energy, retail, and oil & gas. Ndidi has spearheaded innovative projects, including vulnerability testing for 5G campus networks, and her work focuses on applying machine learning to advance communication technologies.



Currently pursuing her Ph.D. in Electrical and Computer Engineering at PVAMU. Ndidi also holds a Master's degree in Electrical and Electronic Engineering from the University of Port Harcourt, Nigeria, and a Bachelor's degree in Electronic Engineering from the University of Nigeria, Nsukka. She has earned certifications in applied data science and machine learning.

CAJETAN M. AKUJUOBI, P.E., F.I.A.A.M., is an Electrical and Computer Engineering Professor and the former Vice President for Research and Dean of Graduate Studies at Prairie View A&M University (PVAMU). He is the founder and the Executive Director of the Center of Excellence for Communication Systems Technology Research (CECSTR) at PVAMU. He is the founder and Principal Investigator of the SECURE Cybersecurity Center of Excellence at PVAMU. His research interests are 5G and Beyond Broadband Communication Systems, Cybersecurity, Mixed Signals Systems, Compressive Sensing, Signal/Image/Video Processing and Communication Systems. He is a Life Senior member of IEEE, a Senior Member of ISA, a Member of the American Society for Engineering Education (ASEE), a Member of Sigma XI, the Scientific Research Society, and the Texas Society for Biomedical Research (TSBR) Board of Directors and other professional organizations.



Prof. Akujobi is the author of many books and book chapters. He has published over 100 peer-reviewed papers and journals. He received a B.S. in Electrical and Electronics Engineering from Southern University, Baton Rouge, Louisiana, in 1980. M.S. in Electrical and Electronics Engineering, Tuskegee University, Tuskegee, Alabama, 1983. M.B.A., Hampton University, Hampton, Virginia 1987. Ph.D. Electrical Engineering, George Mason University, Fairfax, Virginia 1995.

MOHAMED CHOUIKHA is an Executive Professor in the Department of Electrical and Computer Engineering at Prairie View A&M University. He is the Chief Scientist/Executive Director of the SECURE Cybersecurity Center of Excellence. He was the founding Director of the Intelligent Community Center of Academic Excellence, the founding and first Director of the Center of Applied High-Performance Computing, and one of the four founding Directors of the Washington Academy of Biomedical Engineering. He has been a consultant to several companies in the Washington, DC area and was a Board member of Quateams Inc.



Prof. Mohamed F. Chouikha received his B.S. in Electrical Engineering from the Prague Polytechnic University in the Czech Republic and his M.S. and Ph.D. in Electrical Engineering from the University of Colorado in Boulder. He was an Electrical Engineer at the Societe Tunisienne Des Phosphates De Gafsa from 1988 to August 2018. His research interests are in Hardware Systems Security, Cybersecurity, and Control Systems. He has published over 100 peer-reviewed papers and journals. He is a Senior member of IEEE.